



100CT-TTL

**Torque Tool Calibration Transducers,
L Series**



PRODUCT DETAILS

- Built-in L-bracket for mounting perpendicular to your surface
- Requires detachable cable Part: 10293
- Mounting holes drilled for 5/16" bolts, 3.25" on center

PRODUCT ATTRIBUTES

Product	MODEL	 N·m	 lbf·in		 lbf·ft		 kgf·cm			
10011	TT 100IO			10 - 100 ozf.in		7.0 - 70.6 cNM				1/4 in
10012	TT 250IO			25 - 250 ozf.in		17.7 - 177 cNM				1/4 in
10013	TT 400IO			40 - 400 ozf.in		28 - 280 cNM				1/4 in
10257	STT-L 10I		1-10 lbf·in	16 - 160 ozf.in		11.3 - 113 cNM	1.15-11.5 kgf·cm			0.25 in
10258	STT-L 50I	0.56-5.6 N·m	5-50 lbf·in		0.4-4 lbf·ft		5.6-57 kgf·cm			0.25 in
10259	STT-L 100I	1.13-11.3 N·m	10-100 lbf·in		0.83-8.3 lbf·ft		11.5-115 kgf·cm	11.5-115 kgf·m		0.375 in
10260	STT-L 300I	3.4-34 N·m	30-300 lbf·in		2.5-25 lbf·ft		34.5-345 kgf·cm			0.375 in
10261	STT-L 80	10.58-108.5 N·m	96-960 lbf·in		8-80 lbf·ft		110.6-1106 kgf·cm		0.5 in	
10262	STT-L 150	20.3-203.4 N·m	180-1800 lbf·in		15-150 lbf·ft		207.4-2073.8 kgf·cm		0.5 in	
10263	STT-L 250	34-340 N·m	300-3000 lbf·in		25-250 lbf·ft		345.6-3456.4 kgf·cm		0.75 in	
10264	STT-L 600	81.3-813.5 N·m	60-600 lbf·in		60-600 lbf·ft			8.3-83 kgf·m	0.75 in	